

# Capacity Allocators

## APPENDIX A - LIBERTY UTILITIES

Type	% of Peak Day Requirements			% of Total Capacity		
	Pipeline	Storage Withdrawal	Peaking	Pipeline	Storage Withdrawal	Peaking
Residential General	52.98%	12.41%	34.61%	0.50%	0.33%	0.33%
Residential Heating	42.41%	15.20%	42.39%	71.35%	72.07%	72.07%
C&I Small LLF	39.17%	16.05%	44.77%	6.97%	8.04%	8.04%
C&I Medium LLF	40.79%	15.63%	43.59%	12.26%	13.24%	13.24%
C&I Large LLF	42.08%	15.28%	42.63%	2.09%	2.14%	2.14%
C&I Small HLF	61.07%	10.27%	28.66%	1.01%	0.48%	0.48%
C&I Medium HLF	68.97%	8.19%	22.84%	2.54%	0.85%	0.85%
C&I Large HLF	46.10%	14.22%	39.67%	3.28%	2.85%	2.85%
High Load Factor	54.73%	11.95%	33.32%	7.33%	4.51%	4.51%
Low Load Factor	41.92%	15.33%	42.75%	92.67%	95.49%	95.49%
<b>Total</b>				<b>100%</b>	<b>100%</b>	<b>100%</b>